









About ACE Classic Pro

ACE Classic Pro is a mid segment variant of the ACE family that has enhanced monitoring and security features to let you incessantly communicate with your Head Office. It has multiple ports for multiple connections so that you can have a stable connection throughout.

ACE Classic Pro is the cost beneficial solution to connect all your distributed office networks to your Head Office and live track all the traffic through these offices. It also enables you to remotely connect to your main server through advanced VPN technology. It allows you to achieve 100% Uptime through various advanced inbuilt features like Bandwidth Aggregation and Multilink Failover so you achieve increased productivity.

Features	ACE Classic Pro
Bandwidth Aggregation	Yes
Failover	Yes
Policy Routing	Yes
No. Of Users	~20
SIM Slot	1
WAN Ports	2
LAN Ports	3
QoS Support	Yes
WiFi Radio	2T2R
USB Port	1
SSL VPN	3
IPSec VPN	5
GRE Tunnel	2
DNS & DHCP	Yes
Dimensions (mm)	130 x 90 x 25

Product Features

- (01) Bandwidth Aggregation, Internet Failover and Load Balancing
- (02) Seamless Integration with existing networks
- (93) Live tracking and management of all branch offices from your Head office
- Drop in placement support for 100% uptime of existing MPLS/LL/VSAT networks
- (05) Supports PPPoE, Static and DHCP WAN configurations
- Remote Syslog, SNMP, DDNS support
- (07) Integrated wireless access point, supporting 802.11 b/g/n
- (08) Secure SSL/IPSec and GRE Tunnel VPN Support
- (9) WEP, WPA & WPA2 wireless security
- (10) Quality of Service (QoS) sup port with predefined P2P Blocking
- (11) Can be easily configured to work with any brand of UTM
- (12) Secure 3G/4G support over USB and sim card slot







Bandwidth Aggregation and Load Balance



Secure VPN Tunnel



Multilink Auto Failover



Ethernet WAN, 4G Sim & USB Modem



SD-WAN Integration









Phone : +91 876 236 2577 / +91 80 4212 0774

Mail : info@anexgate.com
Website : www.anexgate.com



#21/2, Bhattarahalli, Old Madras Road,14 KM, K.R. Puram, Bangalore-560 049. (INDIA)

HARDWARE FEATURES	0.40.440010
Interface	3 10/100Mbps LAN Ports, 2 10/100Mbps WAN Port, 1 SIM Card Slot
Button	Reset Button
External Power Supply	12V/1A
Dimensions (WxDxH)	5.2 x 3.25 x 1.2 in. (130 x 80 x 29 mm)
Antenna	V4/V2/V1: 2 Detachable 4G LTE Antennas
WIRELESS FEATURES	IEEE 802.11b/g/n 2.4GHz
Wireless Standards	2.4GHz
Wireless Reception Sensitivity	2.4G: 11g 54M: -76dBm
	11n HT20: -73dBm
	11n HT40: -67dBm
4G Antenna Frequency Range	800MHz-960MHz
	1880MHz-1930MHz
V.S.W.R	<=2.0
Gain	2.0 dBi
Polarization Vertical Impedence	50 Ohm
Maximum Input Power	10W
4G Data Speeds	LTE-FDD Max 100Mbps (DL) Max 50Mbps (UL)
	LTE-TDD Max 61Mbps (DL)Max18Mbps (UL)
Transmit Power	CE: <20dBm(2.4GHz), <23dBm(5GHz)
Wireless Functions	Enable/Disable Wireless Radio, WMM,
	Wireless Statistics
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Wireless Security	FDD LTE: B1/B3
	TDD LTE: B38/B39/B40/B41
	TDSCDMA: B34/B39
	WCDMA: B1
	CDMA2000 1x/EVDO: BC0
	GSM: 900/1800MHz
SOFTWARE FEATURES	
Quality of Service	Quality of Service Bandwidth Control, Interface and User based
Operating Modes	3G/4G Router, Wireless Router, Load Balancer, Aggregator, VPN Clie
WAN Type	Dynamic IP/Static IP/PPPoE/4G/3G
Management	Access Control, Local Management, Remote Management
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, DMZ
Dynamic DNS	DynDns, NO-IP
VPN Pass-Through	GRE IPSec VPN , SSL VPN
VPN	GRE IPSec VPN , SSL VPN
Access Control	Domain Filter, Time based Rules
Firewall Security	DoS, SPI Firewall, IP Address Filter/Domain Filter,
	IP and MAC Address Binding
Protocols	Supports IPv4 and IPv6
IPSec VPN	Supports up to 10 IPSec VPN tunnels
OTHERS	
Certification	CE, RoHS
Package Contents	AnexGATE ACE Classic Pro



	RJ45 Ethernet Cable
	Power Adapter
	SIM Card Jacket
	Quick Installation Guide
System Requirements	Windows, MacOS, Linux
	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browsers or higher
	SIM Card
Wireless Security	Operating Temperature: 0C 42C
	Storage Temperature: -32C - 65C
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing